Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	19211194	
Valid tyre size	18 x 6.50 - 8	
LI / SI / PR	66 A4 / 77 A4, 6 PR	
TL/TT	TL	
Brand	Kenda	
Tread pattern	K500 Super Turf	



Notes and features

- For professional use on lawns.
- Very good wear properties and increased puncture resistance.
- The rounded tyre shoulder prevents lawn damage.

Bohnenkamp Moving Professionals

Technical Informations

Item number	19211194
EAN	5707562278506
Valid tyre size	18 x 6.50 - 8
LI / SI / PR	66 A4 / 77 A4, 6 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K500 Super Turf
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	3,77
Recommended rim size	5.375
Maximum air pressure [bar].	2,80
Section width (mm)	170
Outer diameter of tyre [mm].	460
Rolling circumference [mm].	1373
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
66 A4	300	20	Drive Wheel	2,80	
77 A4	412	20	Free Rolling	2,80	