

TYRES

Product group	Tyres
Item number	19211209
Valid tyre size	18 x 8.50 - 8
LI / SI / PR	76 A4 / 88 A4, 8 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K505



Bohnenkamp
Moving Professionals

Notes and features

- Tyre for professional use on grass and garden areas.
- Modern tread pattern design with maximum grip.
- High puncture resistance and increased durability due to more rubber on the contact areas.

Technical Informations

Item number	19211209
EAN	5707562548425
Valid tyre size	18 x 8.50 - 8
LI / SI / PR	76 A4 / 88 A4, 8 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K505
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	5,75
Recommended rim size	7.00
Maximum air pressure [bar].	1,50
Section width (mm)	211
Outer diameter of tyre [mm].	455
Rolling circumference [mm].	1358
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
76 A4	400	20	Drive Wheel	1,50	
88 A4	560	20	Free Rolling	1,50	