Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	19211214	
Valid tyre size	18 x 9.50 - 8	
LI / SI / PR	70 A4 / 81 A4, 4 PR	
TL/TT	TL	
Brand	Kenda	
Tread pattern	K500 Super Turf	



Notes and features

- For professional use on lawns.
- Very good wear properties and increased puncture resistance.
- The rounded tyre shoulder prevents lawn damage.

Bohnenkamp Moving Professionals

Technical Informations

Item number	19211214
EAN	5707562128504
Valid tyre size	18 x 9.50 - 8
LI / SI / PR	70 A4 / 81 A4, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K500 Super Turf
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	5,43
Recommended rim size	7.001
Maximum air pressure [bar].	1,70
Section width (mm)	236
Outer diameter of tyre [mm].	462
Rolling circumference [mm].	1379
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
70 A4	335	20	Drive Wheel	1,70	
81 A4	462	20	Free Rolling	1,70	