Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	19211215	
Valid tyre size	18 x 9.50 - 8	
LI / SI / PR	70 A4 / 81 A4, 4 PR	
TL/TT	TL	
Brand	Kenda	
Tread pattern	K357	



Notes and features

• Versatile traction tyre.

• Ideal for use on compact tractors and single-axle tractors.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Iten number1921215EAN507562330082Vald tyre size88 950-8L/JS/PR704/81A4.4PRTLTT704/81A4.4PRBrandKodaStoragetament837AristaticNoAristaticNoTyre olourBickEC regulation number62 106Rendementering700Antigetament1,00Aristatic9.0Brand1,00Aristation9.0Aristation1,00Brandementering1,00Aristation1,00		
Valid tyre sizeFrank and the second seco	Item number	19211215
Li / Si / PRCi / Si /	EAN	5707562330082
TLTTTLTLTLBrandKendaTread patternKa57AntistaticNoFyre colourBlackECE regulation numberECE 106Retogewicht [kg] (gült)0.25Antistatic1.01Maximun air pressure [data]1.70Section vidth (mm)34Antistatic1.30Number of lugs1.30Sunder of lugs1.30Sunder of lugs1.30Sunder of lugs1.30Sunder of lugs1.30Sunder of lugs1.30Sunder of lugs1.52	Valid tyre size	18 × 9.50 - 8
FrandKendaBrandKendaTread patternK357AntistaticNoDialSecondTyre colourBackBechSecondFer gulation numberSecondOttogewicht [kg] (gült)g)OlNoSecondMaximum air pressure [back]JinOuter diameter of tyre [mainSecondNumber of lugsIsaNumber of lugsIsaSecond LugsSecondSecond LugsSecond Lug	LI / SI / PR	70 A4 / 81 A4, 4 PR
Tread patternK357Tread patternK357AntistaticNoTyre colourBiackBiackCE 106Ketogewicht [kg] (güttg)6.25Recommended rim size7.00Maximum air pressure [bai]1.70Section width (mm)3.40Colure diameter of tyre [mm]3.90Number of Lugs1.90Mumber of Lugs1.90Support (Lugs)1.90Support (Lugs) <t< th=""><th>TL/TT</th><th>TL</th></t<>	TL/TT	TL
AntistaticNoAntistaticNoTyre colourBlackBickCE 106Ecc regulation number6.25Nettogewich [kg] (ültig)0.30Recommended rim size7.00Maximun air pressure [bas]0.30Section width (mm)0.34Guter diameter of tyre [mm]1.30Number of lugs1.30I substruction of tyre [mm]1.30Lugs width (mm)1.30Section width (mm)1.30Substruction of tyre [mm]1.30Substruction of tyre [mm]1.30Substruc	Brand	Kenda
Tyre colourBlackECE regulation numberECE 106Nettogewicht [kg] (gültig)6,25Recommended rim size7.00Maxinum air pressure [bai]1,70Section width (mm)234Outer diameter of tyre [mm]473Rolling circumference [mm]130Number of lugs11x2Lug width (mm)15,5	Tread pattern	K357
ECE regulation numberECE 106Nettogewicht [kg] (gült)g6,25Recommended rim size7.00Maximum air pressure [ba]1,70Section width (mm)234Outer diameter of tyre [mm]4/3Rolling circumference [mm]1800Number of lugs11x2Lug width (mm)15,5	Antistatic	No
Nettogewicht [kg] (gültig)6,25Recommended rim size7.00Maximum air pressure [ba]1,70Section width (mm)234Outer diameter of tyre [mm]473Rolling circumference [mm]1380Number of lugs13,20Lug width (mm)15,5	Tyre colour	Black
Recommended rim size7.00Maximum air pressure [bar]1.70Section width (mm)34Outer diameter of tyre [mm]473Rolling circumference [mm]1.80Number of lugs1.1x2	ECE regulation number	ECE 106
Maximum air pressure [ban]1,70Section width (mm)234Outer diameter of tyre [mm]473Rolling circumference [mm]1380Number of lugs11x2Lug width (mm)15,5	Nettogewicht [kg] (gültig)	6,25
Section width (mm)234Outer diameter of tyre [mm]473Rolling circumference [mm]1380Number of lugs11x2Lug width (mm)15,5	Recommended rim size	7.001
Outer diameter of tyre [mm].473Rolling circumference [mm].1380Number of lugs11x2Lug width (mm).15,5	Maximum air pressure [bar].	1,70
Rolling circumference [mm] 1380 Number of lugs 11x2 Lug width (mm) 15,5	Section width (mm)	234
Number of lugs 11x2 Lug width (mm) 15,5	Outer diameter of tyre [mm].	473
Lug width (mm) 15,5	Rolling circumference [mm].	1380
	Number of lugs	11x2
E-Ready No	Lug width (mm)	15,5
	E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
70 A4	335	20	Drive Wheel	1,70	
81 A4	462	20	Free Rolling	1,70	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.