Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	19211232
Valid tyre size	AT 22 x 11 - 8
LI / SI / PR	43 F, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K290 Scorpion



Notes and features

• Universal ATV and quad tyre.

The evenly spaced blocks on the tread enable optimal off-• road use.

Bohnenkamp Moving Professionals

Technical Informations

	40044000
Item number	19211232
EAN	5707562128870
Valid tyre size	AT 22 x 11 - 8
LI / SI / PR	43 F, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K290 Scorpion
Star Rating	**
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 75
Nettogewicht [kg] (gültig)	5,96
Recommended rim size	8.5
Permitted rim size	9.0
Maximum air pressure [bar].	0,35
Section width (mm)	250
Outer diameter of tyre [mm].	550
Tread depth (mm)	12,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
43 F	155	80		0,35	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.