

TYRES

Product group	Tyres	
Item number	19211236	
Valid tyre size	5.00 - 8	
LI / SI / PR	64 A8 / 75 A8, 6 PR	
TL/TT	тт	
Brand	Kenda	
Tread pattern	K402	



Notes and features

• Tyre for use in gardening and landscaping.

• The treadless design protects the soil effectively.



Technical Informations

Item number	19211236
EAN	4040658084638
Valid tyre size	5.00 - 8
Alternative size 1	140/85-8
LI / SI / PR	64 A8 / 75 A8, 6 PR
TL/TT	ТТ
Brand	Kenda
Tread pattern	K402
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	2,95
Recommended rim size	3.75
Permitted rim size	3.00
Maximum air pressure [bar].	4,10
Section width (mm)	145
Outer diameter of tyre [mm].	453
Rolling circumference [mm].	1352
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
64 A8	280	40	Drive Wheel	4,10	
75 A8	387	40	Free Rolling	4,10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.