

TYRES

Product group	Tyres
Item number	19211251
Valid tyre size	6.00 - 9
LI / SI / PR	10 PR
TL/TT	тт
Brand	Kenda
Tread pattern	K311



Notes and features

• The Kenda K311 was specially developed for use on agricultural transport equipment.



Technical Informations

Item number	19211251
EAN	5707562332512
Valid tyre size	6.00 - 9
LI / SI / PR	10 PR
TL/TT	тт
Brand	Kenda
Tread pattern	K311
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	5,88
Recommended rim size	4.00
Maximum air pressure [bar].	6,90
Section width (mm)	166
Outer diameter of tyre [mm].	528
Rolling circumference [mm].	1576
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	2100	10		6,90	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.