

## **TYRES**

Product group	Tyres	
Item number	19211274	
Valid tyre size	20 x 10.00 - 10	
LI / SI / PR	74 A4 / 85 A4, 4 PR	
TL/TT	TL	
Brand	Kenda	
Tread pattern	K513	



## **Notes and features**

- The Kenda K513 is a tyre for the professional maintenance of lawns.
- Its tread blocks have sipes to provide good traction and consequently optimum soil protection.
- The tyre can be used on slopes and provide good grip in dry as well as wet weather conditions.
- Due to the large contact area and the durable rubber compound, the tyre is particularly low-wear and durable.



## **Technical Informations**

Item number	19211274
EAN	5707562337432
Valid tyre size	20 x 10.00 - 10
LI / SI / PR	74 A4 / 85 A4, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K513
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	6,83
Recommended rim size	7.00
Maximum air pressure [bar].	1,50
Section width (mm)	235
Outer diameter of tyre [mm].	510
Rolling circumference [mm].	1522
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
74 A4	375	20	Drive Wheel	1,50	
85 A4	515	20	Free Rolling	1,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.