

TYRES

Product group	Tyres
Item number	19211281
Valid tyre size	20 x 12.00 - 10
LI / SI / PR	78 A4 / 89 A4, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K516



Notes and features

• Specially designed tyre for use on ride-on mowers.



Technical Informations

Item number	19211281
EAN	5707562380094
Valid tyre size	20 x 12.00 - 10
LI / SI / PR	78 A4 / 89 A4, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K516
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	6,84
Recommended rim size	9.75
Permitted rim size	8.50
Maximum air pressure [bar].	1,40
Section width (mm)	287
Outer diameter of tyre [mm].	500
Rolling circumference [mm].	1492
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
78 A4	425	20	Drive Wheel	1,40	
89 A4	580	20	Free Rolling	1,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.