

TYRES

| | |
|-----------------|---------------------|
| Product group | Tyres |
| Item number | 19211282 |
| Valid tyre size | 20.5 x 8.00 - 10 |
| LI / SI / PR | 65 A4 / 76 A4, 4 PR |
| TL/TT | TL |
| Brand | Kenda |
| Tread pattern | K513 |



Notes and features

- The Kenda K513 is a tyre for the professional maintenance of lawns.
- Its tread blocks have sipes to provide good traction and consequently optimum soil protection.
- The tyre can be used on slopes and provide good grip in dry as well as wet weather conditions.
- Due to the large contact area and the durable rubber compound, the tyre is particularly low-wear and durable.

Technical Informations

| | |
|------------------------------|---------------------|
| Item number | 19211282 |
| EAN | 5707562383002 |
| Valid tyre size | 20.5 x 8.00 - 10 |
| LI / SI / PR | 65 A4 / 76 A4, 4 PR |
| TL/TT | TL |
| Brand | Kenda |
| Tread pattern | K513 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 6,49 |
| Recommended rim size | 6.00 |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 213 |
| Outer diameter of tyre [mm]. | 522 |
| Rolling circumference [mm]. | 1640 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 65 A4 | 290 | 20 | Drive Wheel | 1,60 | |
| 76 A4 | 400 | 20 | Free Rolling | 1,60 | |