Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	19211306
Valid tyre size	AT 24 x 9 - 11
LI / SI / PR	33 F, 2 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K530 Pathfinder



Notes and features

- ATV and quad tyre.
- Optimum use on the road.

• Tread pattern layout enables good traction.

Bohnenkamp Moving Professionals

Technical Informations

Item muchen	10011000
Item number	19211306
EAN	5707562129204
Valid tyre size	AT 24 x 9 - 11
LI / SI / PR	33 F, 2 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K530 Pathfinder
Star Rating	**
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 75
Nettogewicht [kg] (gültig)	6,77
Recommended rim size	7.0
Permitted rim size	7.5
Maximum air pressure [bar].	0,35
Section width (mm)	229
Outer diameter of tyre [mm].	597
Tread depth (mm)	12,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
33 F	115	80		0,35	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.