

TYRES

Product group	Tyres	
Item number	19211308	
Valid tyre size	5.00 - 12	
LI / SI / PR	49 A4 / 60 A4, 4 PR	
TL/TT	тт	
Brand	Kenda	
Tread pattern	K365	



Notes and features

• Traction tyre for compact tractors and single-axle tractors.



Technical Informations

Item number	19211308
EAN	5707562332055
Valid tyre size	5.00 - 12
LI / SI / PR	49 A4 / 60 A4, 4 PR
TL/TT	тт
Brand	Kenda
Tread pattern	K365
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	6,48
Recommended rim size	4.00
Maximum air pressure [bar].	2,00
Section width (mm)	132
Outer diameter of tyre [mm].	580
Rolling circumference [mm].	1731
Tread depth (mm)	23,7
Number of lugs	12x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
49 A4	185	20	Drive Wheel	2,00	
60 A4	250	20	Free Rolling	2,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.