

TYRES

Product group	Tyres	
Item number	19211330	
Valid tyre size	24 x 13.00 - 12	
LI / SI / PR	96 A4 / 108 A4, 6 PR	
TL/TT	TL	
Brand	Kenda	
Tread pattern	K507	



Notes and features

- The Kenda K507 was developed for heavy-duty mowing equipment and is suited to applications on golf courses and other lawn areas.
- The big contact area provides good ride comfort and protects the soil.
- Its special rubber compound and the tread pattern with over 70% contact area guarantee good protection against damages and long durability for the tyre.



Technical Informations

Item number	19211330
EAN	5707562279794
Valid tyre size	24 x 13.00 - 12
LI / SI / PR	96 A4 / 108 A4, 6 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K507
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	11,93
Recommended rim size	10.50
Maximum air pressure [bar].	1,90
Section width (mm)	333
Outer diameter of tyre [mm].	610
Stat. radius (SLR) [mm]	270
Rolling circumference [mm].	1780
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
96 A4	710	20	Drive Wheel	1,90	
108 A4	1000	20	Free Rolling	1,90	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.