Bohnenkamp Moving Professionals

16.11.2024

TYRES

Product group	Tyres	
Item number	19211336	
Valid tyre size	26 x 12.00 - 12	
LI / SI / PR	87 A4 / 99 A4, 4 PR	
TL/TT	TL	
Brand	Kenda	
Tread pattern	K505	



Notes and features

- Tyre for professional use on grass and garden areas.
- Modern tread pattern design with maximum grip.
- High puncture resistance and increased durability due to more rubber on the contact areas.

Bohnenkamp Moving Professionals

Technical Informations

Item number	19211336
EAN	5707562265681
Valid tyre size	26 x 12.00 - 12
Alternative size 1	300/60-12
LI / SI / PR	87 A4 / 99 A4, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K505
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	11,91
Recommended rim size	10.50
Maximum air pressure [bar].	1,50
Section width (mm)	307
Outer diameter of tyre [mm].	645
Rolling circumference [mm].	1925
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
87 A4	545	20	Drive Wheel	1,50	
99 A4	775	20	Free Rolling	1,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.