

TYRES

Product group	Tyres
Item number	19211354
Valid tyre size	215 / 60 - 14
LI / SI / PR	76 A6 / 87 A6, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K505



Notes and features

- Tyre for professional use on grass and garden areas.
- Modern tread pattern design with maximum grip.
- High puncture resistance and increased durability due to more rubber on the contact areas.

Technical Informations

Item number	19211354
EAN	5707562439327
Valid tyre size	215 / 60 - 14
Alternative size 1	24x8.50-14
LI / SI / PR	76 A6 / 87 A6, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K505
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	8,61
Recommended rim size	7.00JA
Maximum air pressure [bar].	2,00
Section width (mm)	216
Outer diameter of tyre [mm].	607
Stat. radius (SLR) [mm]	278
Rolling circumference [mm].	1825
Tread depth (mm)	8,8
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
76 A6	400	30	Drive Wheel	2,00	
87 A6	545	30	Free Rolling	2,00	