

TYRES

Product group	Tyres
Item number	19211357
Valid tyre size	212 / 80 - 15
LI / SI / PR	68 A6 / 79 A6
TL/TT	TL
Brand	Kenda
Tread pattern	K505



Notes and features

- Tyre for professional use on grass and garden areas.
- Modern tread pattern design with maximum grip.
- High puncture resistance and increased durability due to more rubber on the contact areas.



Technical Informations

Item number	19211357
EAN	5707562435923
Valid tyre size	212 / 80 - 15
LI / SI / PR	68 A6 / 79 A6
TL/TT	TL
Brand	Kenda
Tread pattern	K505
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	12,38
Recommended rim size	7.00JA
Maximum air pressure [bar].	1,60
Section width (mm)	217
Outer diameter of tyre [mm].	721
Stat. radius (SLR) [mm]	338
Rolling circumference [mm].	2135
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
68 A6	315	30	Drive Wheel	1,60	
79 A6	437	30	Free Rolling	1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.