

## **TYRES**

Product group	Tyres	
Item number	19211360	
Valid tyre size	33 x 12.50 - 16.5	
LI / SI / PR	97 A4 / 109 A4, 4 PR	
TL/TT	TL	
Brand	Kenda	
Tread pattern	K500 Super Turf	



## Notes and features

- For professional use on lawns.
- Very good wear properties and increased puncture resistance.
- The rounded tyre shoulder prevents lawn damage.



## **Technical Informations**

Item number	19211360
EAN	5707562269153
Valid tyre size	33 x 12.50 - 16.5
Alternative size 1	320/65-16.5
LI / SI / PR	97 A4 / 109 A4, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K500 Super Turf
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	23,82
Recommended rim size	9.75
Maximum air pressure [bar].	2,10
Section width (mm)	318
Outer diameter of tyre [mm].	838
Stat. radius (SLR) [mm]	383
Rolling circumference [mm].	2501
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
97 A4	730	20	Drive Wheel	2,10	
109 A4	1030	20	Free Rolling	2,10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.