

## **TYRES**

Product group	Tyres	
Item number	19266050	
Valid tyre size	4.80 / 4.00 - 8	
LI / SI / PR	70 M, 6 PR	
TL/TT	тт	
SET	Tube	
Brand	Kenda	
Tread pattern	K371	



## Notes and features

• High-speed trailer tyre.



## **Technical Informations**

Item number	19266050
EAN	5707562497938
Valid tyre size	4.80 / 4.00 - 8
LI / SI / PR	70 M, 6 PR
TL/TT	тт
SET	Tube
Valve designation	TR 13
Ventilposition	lateral
Brand	Kenda
Tread pattern	K371
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	2,45
Recommended rim size	3.75
Permitted rim size	2.50A
Maximum air pressure [bar].	5,90
Section width (mm)	119
Outer diameter of tyre [mm].	403
Stat. radius (SLR) [mm]	176
Rolling circumference [mm].	1215
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
70 M	335	130		5,90	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.