

TYRES

| Product group | Tyres |
|-----------------|-----------------|
| Item number | 19266056 |
| Valid tyre size | 18.5 x 8.50 - 8 |
| LI / SI / PR | 78 M, 6 PR |
| TL/TT | TL |
| Brand | Kenda |
| Tread pattern | K368 |



Notes and features

• High-speed trailer tyre.



Technical Informations

| Item number | 19266056 |
|------------------------------|-----------------|
| EAN | 5707562289786 |
| Valid tyre size | 18.5 x 8.50 - 8 |
| Alternative size 1 | 215/60-8 |
| LI / SI / PR | 78 M, 6 PR |
| TL/TT | TL |
| Brand | Kenda |
| Tread pattern | K368 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54 |
| Nettogewicht [kg] (gültig) | 6,33 |
| Recommended rim size | 7.001 |
| Maximum air pressure [bar]. | 3,50 |
| Section width (mm) | 220 |
| Outer diameter of tyre [mm]. | 462 |
| E-Ready | No |

Load capacity

| Inde | x Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|------|----------------------|--------------|---------------|-----------------------------|--------------|
| 78 1 | 425 | 130 | | 3,50 | _ |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.