

TYRES

Product group	Tyres
Item number	19266060
Valid tyre size	5.00 - 10
LI / SI / PR	84 M, 8 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K364



Notes and features

• High-speed trailer tyre.



Technical Informations

Item number	19266060
EAN	5707562374505
Valid tyre size	5.00 - 10
LI / SI / PR	84 M, 8 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K364
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	6,05
Recommended rim size	3.5
Permitted rim size	3.0
Maximum air pressure [bar].	4,50
Section width (mm)	138
Outer diameter of tyre [mm].	513
Stat. radius (SLR) [mm]	244
Rolling circumference [mm].	1560
E-Ready	No

Load capacity

Ind	ex	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
84	М	500	130		4,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.