

TYRES

| Product group | Tyres |
|-----------------|---------------|
| Item number | 19266067 |
| Valid tyre size | 195 / 50 B 10 |
| LI / SI / PR | 98 N, 8 PR |
| TL/TT | TL |
| Brand | Kenda |
| Tread pattern | K399 Loadstar |



Notes and features

- The Kenda K399 Loadstar is a diagonal tyre for highspeed trailers.
- Thanks to its innovative rubber compound, it provides excellent wear resistance and low rolling resistance.
- The flat tread pattern design offers high tensile stability.



Technical Informations

| Item number | 19266067 |
|------------------------------|---------------|
| EAN | 5707562128405 |
| Valid tyre size | 195 / 50 B 10 |
| Alternative size 1 | 18x.8.0-10 |
| LI / SI / PR | 98 N, 8 PR |
| TL/TT | TL |
| Brand | Kenda |
| Tread pattern | K399 Loadstar |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54 |
| Nettogewicht [kg] (gültig) | 5,45 |
| Recommended rim size | 6.001 |
| Maximum air pressure [bar]. | 6,00 |
| Section width (mm) | 185 |
| Outer diameter of tyre [mm]. | 460 |
| Stat. radius (SLR) [mm] | 210 |
| Rolling circumference [mm]. | 1372 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 98 N | 750 | 140 | | 6,00 | |
| | 825 | 80 | | 6,00 | |
| | 851 | 65 | | 6,00 | |
| | 938 | 40 | | 6,00 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.