

TYRES

Product group	Tyres
Item number	19266102
Valid tyre size	155 / 70 R 12 C
LI / SI / PR	104 / 102 N
TL/TT	TL
Brand	Kenda
Tread pattern	KR101 MasterTrail 3G



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- The Kenda KR101 MasterTrail 3G is a tyre for single axle car trailers, tandem, tridem and other heavy trailers.
- The strong casing enables very high loading capacities.
- Due to its tread pattern, the tyre provides low rolling resistance, good wet grip and low noise.
- The high number of sipes ensures good dispersion of water, slush and snow for excellent driving performance all year round.
- The reinforced inner liner construction keeps the tyre particularly airtight and puncture-proof.

Technical Informations

Item number	19266102
EAN	5707562674544
Valid tyre size	155 / 70 R 12 C
LI / SI / PR	104 / 102 N
TL/TT	TL
Brand	Kenda
Tread pattern	KR101 MasterTrail 3G
M+S	M+S
Rolling resistance	B
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	5,90
Recommended rim size	4.50J
Permitted rim size	4J, 5J
Maximum air pressure [bar].	6,50
Section width (mm)	157
Outer diameter of tyre [mm].	527
Stat. radius (SLR) [mm]	239
Rolling circumference [mm].	1597
Tread depth (mm)	5,8
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
104 N	900	140		6,50	
102 N	850	140		6,50	