

TYRES

Product group	Tyres	
Item number	19266115	
Valid tyre size	145 / 80 R 13	
LI / SI / PR	78 N	
TL/TT	TL	
Brand	Kenda	
Tread pattern	KR209 KargoTrail 3G	



Notes and features

- The Kenda KR209 KargoTrail 3G is a tyre for single axle car trailers and mid-range tandem trailers.
- Due to its tread pattern, the tyre provides low rolling resistance, good wet grip and low noise.
- The high number of sipes ensures good dispersion of water, slush and snow for excellent driving performance all year round.
- The reinforced inner liner construction keeps the tyre particularly airtight and puncture-proof.



Technical Informations

Item number	19266115			
EAN	5707562674445			
Valid tyre size	145 / 80 R 13			
LI / SI / PR	78 N			
TL/TT	TL			
Brand	Kenda			
Tread pattern	KR209 KargoTrail 3G			
M+S	M+S			
Rolling resistance	С			
Wet grip	D			
Rolling noise [db].	69			
Rolling noise level	В			
Antistatic	No			
Tyre colour	Black			
ECE regulation number	ECE 30,ECE 117			
Nettogewicht [kg] (gültig)	5,00			
Recommended rim size	4J			
Permitted rim size	3.50J, 3.50B, 4.00B, 4.50J, 4.50B, 5J			
Maximum air pressure [bar].	3,40			
Section width (mm)	145			
Outer diameter of tyre [mm].	r of tyre [mm]. 562			
Stat. radius (SLR) [mm]	255			
Rolling circumference [mm].	1714			
Tread depth (mm)	5,0			
E-Ready	No			

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
78 N	425	140		3,40	