

TYRES

Product group	Tyres
Item number	19266116
Valid tyre size	155 / 70 R 13
LI / SI / PR	74 N
TL/TT	TL
Brand	Kenda
Tread pattern	KR209 KargoTrail 3G



Notes and features

- The Kenda KR209 KargoTrail 3G is a tyre for single axle car trailers and mid-range tandem trailers.
- Due to its tread pattern, the tyre provides low rolling resistance, good wet grip and low noise.
- The high number of sipes ensures good dispersion of water, slush and snow for excellent driving performance all year round.
- The reinforced inner liner construction keeps the tyre particularly airtight and puncture-proof.

Technical Informations

Item number	19266116
EAN	5707562674452
Valid tyre size	155 / 70 R 13
LI / SI / PR	74 N
TL/TT	TL
Brand	Kenda
Tread pattern	KR209 KargoTrail 3G
M+S	M+S
Rolling resistance	C
Wet grip	D
Rolling noise [db].	69
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 30,ECE 117
Nettogewicht [kg] (gültig)	5,10
Recommended rim size	4.50J
Permitted rim size	4J, 4.00B, 4.50J, 4.50B, 5J, 5.00B
Maximum air pressure [bar].	3,00
Section width (mm)	157
Outer diameter of tyre [mm].	548
Stat. radius (SLR) [mm]	250
Rolling circumference [mm].	1671
Tread depth (mm)	5,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
74 N	375	140		3,00	