

TYRES

| | |
|-----------------|----------------------|
| Product group | Tyres |
| Item number | 19266132 |
| Valid tyre size | 175 R 14 C |
| LI / SI / PR | 99 / 98 N |
| TL/TT | TL |
| Brand | Kenda |
| Tread pattern | KR101 MasterTrail 3G |



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- The Kenda KR101 MasterTrail 3G is a tyre for single axle car trailers, tandem, tridem and other heavy trailers.
- The strong casing enables very high loading capacities.
- Due to its tread pattern, the tyre provides low rolling resistance, good wet grip and low noise.
- The high number of sipes ensures good dispersion of water, slush and snow for excellent driving performance all year round.
- The reinforced inner liner construction keeps the tyre particularly airtight and puncture-proof.

Technical Informations

| | |
|------------------------------|----------------------|
| Item number | 19266132 |
| EAN | 5707562674568 |
| Valid tyre size | 175 R 14 C |
| LI / SI / PR | 99 / 98 N |
| TL/TT | TL |
| Brand | Kenda |
| Tread pattern | KR101 MasterTrail 3G |
| M+S | M+S |
| Rolling resistance | B |
| Wet grip | C |
| Rolling noise [db]. | 72 |
| Rolling noise level | B |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54,ECE 117 |
| Nettogewicht [kg] (gültig) | 8,40 |
| Recommended rim size | 5J |
| Permitted rim size | 4.50J, 5.50J |
| Maximum air pressure [bar]. | 4,50 |
| Section width (mm) | 178 |
| Outer diameter of tyre [mm]. | 634 |
| Stat. radius (SLR) [mm] | 284 |
| Rolling circumference [mm]. | 1921 |
| Tread depth (mm) | 5,8 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 99 N | 775 | 140 | | 4,50 | |
| 98 N | 750 | 140 | | 4,50 | |