

## **TYRES**

| Product group   | Tyres                       |  |
|-----------------|-----------------------------|--|
| Item number     | 19266145                    |  |
| Valid tyre size | 195 / 65 R 15<br>98 N<br>TL |  |
| LI / SI / PR    |                             |  |
| TL/TT           |                             |  |
| Brand           | Kenda                       |  |
| Tread pattern   | KR209 KargoTrail 3G         |  |



## Notes and features

- The Kenda KR209 KargoTrail 3G is a tyre for single axle car trailers and mid-range tandem trailers.
- Due to its tread pattern, the tyre provides low rolling resistance, good wet grip and low noise.
- The high number of sipes ensures good dispersion of water, slush and snow for excellent driving performance all year round.
- The reinforced inner liner construction keeps the tyre particularly airtight and puncture-proof.



## **Technical Informations**

| Item number                  | 19266145            |
|------------------------------|---------------------|
| EAN                          | 5707562674513       |
| Valid tyre size              | 195 / 65 R 15       |
| LI / SI / PR                 | 98 N                |
| TL/TT                        | TL                  |
| Brand                        | Kenda               |
| Tread pattern                | KR209 KargoTrail 3G |
| M+S                          | M+S                 |
| Rolling resistance           | В                   |
| Wet grip                     | D                   |
| Rolling noise [db].          | 69                  |
| Rolling noise level          | В                   |
| Antistatic                   | No                  |
| Tyre colour                  | Black               |
| ECE regulation number        | ECE 30,ECE 117      |
| Nettogewicht [kg] (gültig)   | 7,80                |
| Recommended rim size         | 6J                  |
| Permitted rim size           | 5.50J, 6.50J, 7J    |
| Maximum air pressure [bar].  | 3,40                |
| Section width (mm)           | 200                 |
| Outer diameter of tyre [mm]. | 636                 |
| Stat. radius (SLR) [mm]      | 290                 |
| Rolling circumference [mm].  | 1940                |
| Tread depth (mm)             | 5,5                 |
| E-Ready                      | No                  |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 98 N  | 750                | 140          |               | 3,40                        |              |