

TYRES

Product group	Tyres
Item number	19271061
Valid tyre size	18 x 7 - 8
LI / SI / PR	16 PR
TL/TT	TT
SET	Tube + Flap
Brand	Kenda
Tread pattern	K610 Kinetics



Notes and features

- Pneumatic tyre for forklifts and container stackers.
- Robust and reliable tyre with long service life.
- Excellent traction and large contact area.
- Additional casing reinforcement provides even contact area.

Technical Informations

Item number	19271061
EAN	5707562272573
Valid tyre size	18 x 7 - 8
Alternative size 1	180/70-8
LI / SI / PR	16 PR
TL/TT	TT
SET	Tube + Flap
Valve designation	JS 2
Ventilposition	lateral
Brand	Kenda
Tread pattern	K610 Kinetics
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	10,06
Recommended rim size	4.33R
Maximum air pressure [bar].	10,00
Section width (mm)	168
Outer diameter of tyre [mm].	462
Tread depth (mm)	15,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	2063	25	Load wheel	10,00	
	1650	25	Steering wheel	10,00	