

TYRES

Product group	Tyres
Item number	19271070
Valid tyre size	6.50 - 10
LI / SI / PR	12 PR
TL/TT	тт
SET	Tube + Flap
Brand	Kenda
Tread pattern	K610 Kinetics



Notes and features

- Pneumatic tyre for forklifts and container stackers.
- Robust and reliable tyre with long service life.
- Excellent traction and large contact area.
- Additional casing reinforcement provides even contact area.



Technical Informations

Item number	19271070
EAN	5707562272597
Valid tyre size	6.50 - 10
LI / SI / PR	12 PR
TL/TT	тт
SET	Tube + Flap
Valve designation	JS 2
Ventilposition	lateral
Brand	Kenda
Tread pattern	K610 Kinetics
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	14,04
Recommended rim size	5.0
Maximum air pressure [bar].	9,00
Section width (mm)	182
Outer diameter of tyre [mm].	590
Tread depth (mm)	16,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	2063	25	Load wheel	9,00	
	1650	25	Steering wheel	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.