

TYRES

Product group	Tyres
Item number	19271071
Valid tyre size	23 x 9 - 10
LI / SI / PR	20 PR
TL/TT	TT
SET	Tube + Flap
Brand	Kenda
Tread pattern	K610 Kinetics



Notes and features

- Pneumatic tyre for forklifts and container stackers.
- Robust and reliable tyre with long service life.
- Excellent traction and large contact area.
- Additional casing reinforcement provides even contact area.

Technical Informations

Item number	19271071
EAN	5707562272825
Valid tyre size	23 x 9 - 10
Alternative size 1	225/75-10
LI / SI / PR	20 PR
TL/TT	TT
SET	Tube + Flap
Valve designation	JS 2
Ventilposition	lateral
Brand	Kenda
Tread pattern	K610 Kinetics
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	25,74
Recommended rim size	6.5
Maximum air pressure [bar].	10,00
Section width (mm)	235
Outer diameter of tyre [mm].	590
Tread depth (mm)	18,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	3313	25	Load wheel	10,00	
	2650	25	Steering wheel	10,00	