Bohnenkamp Moving Professionals

15.11.2024

TYRES

Product group	Tyres	
Item number	19271072	
Valid tyre size	18 x 8.50 - 10	
LI / SI / PR	61 A4 / 72 A4, 4 PR	
TL/TT	TL	
Brand	Kenda	
Tread pattern	K514	



Notes and features

• The Kenda K514 is an industrial tyre especially suited to use on Bobcats.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item muchen	10071070
Item number	19271072
EAN	5707562452821
Valid tyre size	18 × 8.50 - 10
Alternative size 1	195/55-10
LI / SI / PR	61 A4 / 72 A4, 4 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K514
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	5,36
Recommended rim size	6.00
Maximum air pressure [bar].	1,50
Section width (mm)	186
Outer diameter of tyre [mm].	462
Stat. radius (SLR) [mm]	209
Rolling circumference [mm].	1382
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
61 A4	257	20		1,50	
72 A4	355	20		1,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.