

TYRES

| | |
|-----------------|---------------|
| Product group | Tyres |
| Item number | 19271080 |
| Valid tyre size | 7.00 - 12 |
| LI / SI / PR | 16 PR |
| TL/TT | TT |
| SET | Tube + Flap |
| Brand | Kenda |
| Tread pattern | K610 Kinetics |



Notes and features

- Pneumatic tyre for forklifts and container stackers.
- Robust and reliable tyre with long service life.
- Excellent traction and large contact area.
- Additional casing reinforcement provides even contact area.

Technical Informations

| | |
|------------------------------|---------------|
| Item number | 19271080 |
| EAN | 5707562272627 |
| Valid tyre size | 7.00 - 12 |
| LI / SI / PR | 16 PR |
| TL/TT | TT |
| SET | Tube + Flap |
| Valve designation | TR 75 A |
| Ventilposition | lateral |
| Brand | Kenda |
| Tread pattern | K610 Kinetics |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 18,99 |
| Recommended rim size | 5.0 |
| Maximum air pressure [bar]. | 10,00 |
| Section width (mm) | 191 |
| Outer diameter of tyre [mm]. | 680 |
| Tread depth (mm) | 17,0 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|----------------|--------------------------|--------------|
| | 2800 | 25 | Load wheel | 10,00 | |
| | 2240 | 25 | Steering wheel | 10,00 | |