

TYRES

Product group	Tyres
Item number	19271082
Valid tyre size	27 x 10 - 12
LI / SI / PR	24 PR
TL/TT	TT
SET	Tube + Flap
Brand	Kenda
Tread pattern	K610 Kinetics



Notes and features

- Pneumatic tyre for forklifts and container stackers.
- Robust and reliable tyre with long service life.
- Excellent traction and large contact area.
- Additional casing reinforcement provides even contact area.

Technical Informations

Item number	19271082
EAN	5707562272658
Valid tyre size	27 x 10 - 12
Alternative size 1	255/75-12
LI / SI / PR	24 PR
TL/TT	TT
SET	Tube + Flap
Valve designation	JS 2
Ventilposition	lateral
Brand	Kenda
Tread pattern	K610 Kinetics
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	30,75
Recommended rim size	8.0
Maximum air pressure [bar].	10,50
Section width (mm)	250
Outer diameter of tyre [mm].	685
Stat. radius (SLR) [mm]	296
Tread depth (mm)	21,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	4845	25	Load wheel	10,50	
	3875	25	Steering wheel	10,50	