

TYRES

Product group	Tyres
Item number	19271088
Valid tyre size	26 x 12.00 - 12
LI / SI / PR	125 A2, 10 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K395 Power Grip



Notes and features

Tyre for skid steer loaders, dumpers and telescopic loaders.



Technical Informations

Item number	19271088
EAN	5707562265698
Valid tyre size	26 x 12.00 - 12
Alternative size 1	305/60-12
LI / SI / PR	125 A2, 10 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K395 Power Grip
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	18,08
Recommended rim size	10.5
Permitted rim size	9.5, 10.0
Maximum air pressure [bar].	4,50
Section width (mm)	304
Outer diameter of tyre [mm].	670
Stat. radius (SLR) [mm]	312
Rolling circumference [mm].	2033
Tread depth (mm)	16,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
125 A2	1650	10		4,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.