

## TYRES

Product group	Tyres
Item number	19271096
Valid tyre size	250 - 15
LI / SI / PR	20 PR
TL/TT	TT
SET	Tube
Brand	Kenda
Tread pattern	K610 Kinetics



## Notes and features

- Pneumatic tyre for forklifts and container stackers.
- Robust and reliable tyre with long service life.
- Excellent traction and large contact area.
- Additional casing reinforcement provides even contact area.

## Technical Informations

Item number	19271096
EAN	5707562272702
Valid tyre size	250 - 15
Alternative size 1	250/70-15
LI / SI / PR	20 PR
TL/TT	TT
SET	Tube
Valve designation	TR 77 A
Ventilposition	lateral
Brand	Kenda
Tread pattern	K610 Kinetics
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	38,08
Recommended rim size	7.5
Maximum air pressure [bar].	10,00
Section width (mm)	240
Outer diameter of tyre [mm].	742
Tread depth (mm)	18,5
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	4844	25	Load wheel	10,00	
	3875	25	Steering wheel	10,00	