

TYRES

Product group	Tyres
Item number	19271097
Valid tyre size	300 - 15
LI / SI / PR	20 PR
TL/TT	TT
SET	Tube + Flap
Brand	Kenda
Tread pattern	K610 Kinetics



Notes and features

- Pneumatic tyre for forklifts and container stackers.
- Robust and reliable tyre with long service life.
- Excellent traction and large contact area.
- Additional casing reinforcement provides even contact area.

Technical Informations

Item number	19271097
EAN	5707562272719
Valid tyre size	300 - 15
Alternative size 1	315/70-15
LI / SI / PR	20 PR
TL/TT	TT
SET	Tube + Flap
Valve designation	TR 177 A
Ventilposition	central
Brand	Kenda
Tread pattern	K610 Kinetics
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	47,98
Recommended rim size	8.0
Maximum air pressure [bar].	9,00
Section width (mm)	290
Outer diameter of tyre [mm].	840
Stat. radius (SLR) [mm]	313
Rolling circumference [mm].	2065
Tread depth (mm)	22,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	6250	25	Load wheel	9,00	
	5000	25	Steering wheel	9,00	