Bohnenkamp Moving Professionals

15.11.2024

TYRES

Product group	Tyres	
Item number	19271098	
Valid tyre size	27 x 8.50 - 15	
LI / SI / PR	96 A2, 6 PR	
TL/TT	TL	
Brand	Kenda	
Tread pattern	K395 Power Grip	



Notes and features

• Tyre for skid steer loaders, dumpers and telescopic loaders.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	19271098
EAN	5707562146348
Valid tyre size	27 x 8.50 - 15
Alternative size 1	220/65-15
LI / SI / PR	96 A2, 6 PR
TL/TT	тι
Brand	Kenda
Tread pattern	K395 Power Grip
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	14,35
Recommended rim size	7.0
Permitted rim size	8.0
Maximum air pressure [bar].	3,10
Section width (mm)	227
Outer diameter of tyre [mm].	674
Stat. radius (SLR) [mm]	322
Rolling circumference [mm].	2073
Tread depth (mm)	12,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
96 A2	710	10		3,10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.