

TYRES

Product group	Tyres	
Item number	19271110	
Valid tyre size	10 - 16.5	
LI / SI / PR	130 A2, 8 PR	
TL/TT	TL	
Brand	Kenda	
Tread pattern	K395 Power Grip	



Notes and features

Tyre for skid steer loaders, dumpers and telescopic loaders.



Technical Informations

Item number	19271110
EAN	5707562128085
Valid tyre size	10 - 16.5
Alternative size 1	270/65-16.5
LI / SI / PR	130 A2, 8 PR
TL/TT	TL
Brand	Kenda
Tread pattern	K395 Power Grip
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	23,80
Recommended rim size	8.25
Maximum air pressure [bar].	3,80
Section width (mm)	274
Outer diameter of tyre [mm].	768
Stat. radius (SLR) [mm]	347
Rolling circumference [mm].	2297
Tread depth (mm)	18,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
130 A2	1900	10		3,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.