

TYRES

Product group	Tyres
Item number	19271120
Valid tyre size	10.00 - 20
LI / SI / PR	16 PR
TL/TT	TT
SET	Tube + Flap
Brand	Kenda
Tread pattern	K610 Kinetics



Notes and features

- Pneumatic tyre for forklifts and container stackers.
- Robust and reliable tyre with long service life.
- Excellent traction and large contact area.
- Additional casing reinforcement provides even contact area.

Technical Informations

Item number	19271120
EAN	5707562272740
Valid tyre size	10.00 - 20
LI / SI / PR	16 PR
TL/TT	TT
SET	Tube + Flap
Ventilposition	central
Brand	Kenda
Tread pattern	K610 Kinetics
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	75,42
Recommended rim size	7.5
Permitted rim size	7.00, 7.50, 8.00
Maximum air pressure [bar].	9,00
Section width (mm)	294
Outer diameter of tyre [mm].	1080
Tread depth (mm)	31,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	6250	25	Load wheel	9,00	
	5000	25	Steering wheel	9,00	