Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	19271121
Valid tyre size	11.00 - 20
LI / SI / PR	18 PR
TL/TT	ТТ
SET	Tube + Flap
Brand	Kenda
Tread pattern	K610 Kinetics



Notes and features

- Pneumatic tyre for forklifts and container stackers.
- Robust and reliable tyre with long service life.
- Excellent traction and large contact area.
- Additional casing reinforcement provides even contact area.

20.09.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number19271121EAN570562272757Valid tyre size11.00-20L/ SI / PR18 PRTL/TTTTSETTube + FlapVentilpositioncentralBrandKendaTread patternK610 KineticsAntistaticNoBlack
Valid tyre size 1.00 - 20 L/ SI / PR 18 PR TL/TT T SET 10b + Flap Ventilposition central Brand Kenda Tread pattern No
LI/SI/PRI8 PRTL/TTTTSETTube FlapVentilpositioncentralBrandKendaTread patternNo
TL/TT T SET Tube + Flap Ventilposition central Brand Kenda Tread pattern K610 Kinetics Antistatic No
SET Tube + Flap Ventilposition central Brand Kenda Tread pattern K610 Kinetics Antistatic No
Ventilposition central Brand Kenda Tread pattern K610 Kinetics Antistatic No
Brand Kenda Tread pattern K610 Kinetics Antistatic No
Tread pattern K610 Kinetics Antistatic No
Antistatic No
Tyre colour Black
ECE regulation number not necessary
Nettogewicht [kg] (gültig) 90,22
Recommended rim size 8.0
Maximum air pressure [bar]. 10,00
Section width (mm) 302
Outer diameter of tyre [mm]. 1110
Tread depth (mm) 32,5
E-Ready No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	7500	25	Load wheel	10,00	
	6000	25	Steering wheel	10,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.