

TYRES

Product group	Tyres
Item number	19271130
Valid tyre size	12.00 - 24
LI / SI / PR	24 PR
TL/TT	TT
SET	Tube + Flap
Brand	Kenda
Tread pattern	K610 Kinetics



Notes and features

- Pneumatic tyre for forklifts and container stackers.
- Robust and reliable tyre with long service life.
- Excellent traction and large contact area.
- Additional casing reinforcement provides even contact area.

Technical Informations

Item number	19271130
EAN	5707562272795
Valid tyre size	12.00 - 24
LI / SI / PR	24 PR
TL/TT	TT
SET	Tube + Flap
Ventilposition	central
Brand	Kenda
Tread pattern	K610 Kinetics
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	119,22
Recommended rim size	8.50
Maximum air pressure [bar].	10,35
Section width (mm)	320
Outer diameter of tyre [mm].	1245
Tread depth (mm)	35,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	9563	25	Load wheel	10,35	
	7650	25	Steering wheel	10,35	