

## TYRES

Product group	Tyres
Item number	19800192
Valid tyre size	6.50 R 16
LI / SI / PR	108 / 107 N, 10 PR
TL/TT	TL
Brand	GT Radial
Tread pattern	Super Traveler 668



Bohnenkamp  
■ ■ ● Moving Professionals

**GT** RADIAL

## Notes and features

- The GT Radial Super Traveller 668 is a tyre for light trucks.
- Its robust tread pattern with 4 circumferential grooves ensures good water displacement and thus safe driving on wet roads.
- The strong tyre shoulder guarantees good stability and protects against premature wear.

## Technical Informations

Item number	19800192
EAN	6932877194534
Valid tyre size	6.50 R 16
LI / SI / PR	108 / 107 N, 10 PR
TL/TT	TL
Brand	GT Radial
Tread pattern	Super Traveler 668
Rolling resistance	D
Wet grip	C
Rolling noise [db].	69
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	16,00
Recommended rim size	5.50F
Maximum air pressure [bar].	5,00
Section width (mm)	185
Outer diameter of tyre [mm].	750
Stat. radius (SLR) [mm]	344
Rolling circumference [mm].	2272
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
108 N	1000	140	Single	5,00	
107 N	975	140	Twin	5,00	