

TYRES

Product group	Tyres	
Item number	19800270	
Valid tyre size	4.00 - 16	
LI / SI / PR	69 A6 / 61 A8, 4 PR	
TL/TT	тт	
Brand	MRL	
Tread pattern	MTF 222	



Notes and features

- The MRL MTF 222 is a front tractor tyre.
- Its typical tread pattern design with 2 centre ribs and open shoulder lugs provides ride comfort, traction and good self-cleaning.
- Strong casing plies guarantee a long service life for the tyre.



Technical Informations

Item number	19800270
EAN	8907375026524
Valid tyre size	4.00 - 16
LI / SI / PR	69 A6 / 61 A8, 4 PR
TL/TT	тт
Brand	MRL
Tread pattern	MTF 222
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	5,20
Recommended rim size	3.00D
Maximum air pressure [bar].	3,40
Section width (mm)	112
Outer diameter of tyre [mm].	630
Stat. radius (SLR) [mm]	305
Rolling circumference [mm].	1880
Tread depth (mm)	11,0
Tyre capacity 75% [ltr.]	10
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
69 A6	325	30		3,40	
61 A8	257	40		3,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.