Bohnenkamp Moving Professionals

15.11.2024

TYRES

| Product group | Tyres | |
|-----------------|---------------------|--|
| Item number | 19800271 | |
| Valid tyre size | 5.00 - 15 | |
| LI / SI / PR | 94 A6 / 90 A8, 6 PR | |
| TL/TT | тт | |
| Brand | MRL | |
| Tread pattern | MIM 374 | |



Notes and features

- The MRL MIM 374 is an agricultural tyre for tractors, which can also be used on backhoe loaders and agricultural trailers.
- Its curved lugs with wide spaces provide good traction, ride comfort, self-cleaning and a long service life.
- The especially wide lugs enable good ground contact for excellent traction on towing machines.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

| Item number | 19800271 |
|------------------------------|---------------------|
| EAN | 8907375029525 |
| Valid tyre size | 5.00 - 15 |
| LI / SI / PR | 94 A6 / 90 A8, 6 PR |
| TL/TT | TT |
| Brand | MRL |
| Tread pattern | MIM 374 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 6,50 |
| Recommended rim size | 3.50D |
| Permitted rim size | 3.00D, 4.00E |
| Maximum air pressure [bar]. | 3,50 |
| Section width (mm) | 145 |
| Outer diameter of tyre [mm]. | 639 |
| Stat. radius (SLR) [mm] | 300 |
| Rolling circumference [mm]. | 1880 |
| Tread depth (mm) | 16,0 |
| Number of lugs | 16x2 |
| Tyre capacity 75% [ltr.] | 14 |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 94 A6 | 670 | 30 | | 3,50 | LLV |
| 90 A8 | 600 | 40 | | 3,50 | LLV |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.