

## TYRES

Product group	Tyres
Item number	19800272
Valid tyre size	4.50 - 16
LI / SI / PR	73 A6 / 65 A8, 4 PR
TL/TT	TT
Brand	MRL
Tread pattern	MTF 222



Bohnenkamp  
■ ■ ● Moving Professionals

## Notes and features

- The MRL MTF 222 is a front tractor tyre.
- Its typical tread pattern design with 2 centre ribs and open shoulder lugs provides ride comfort, traction and good self-cleaning.
- Strong casing plies guarantee a long service life for the tyre.

## Technical Informations

Item number	19800272
EAN	8907375027576
Valid tyre size	4.50 - 16
LI / SI / PR	73 A6 / 65 A8, 4 PR
TL/TT	TT
Brand	MRL
Tread pattern	MTF 222
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	5,50
Recommended rim size	3.00D
Maximum air pressure [bar].	3,10
Section width (mm)	122
Outer diameter of tyre [mm].	655
Stat. radius (SLR) [mm]	305
Rolling circumference [mm].	1955
Tread depth (mm)	11,0
Tyre capacity 75% [litr.]	12
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
73 A6	365	30		3,10	
65 A8	290	40		3,10	