

TYRES

| | |
|-----------------|---------------------|
| Product group | Tyres |
| Item number | 19800274 |
| Valid tyre size | 5.00 - 16 |
| LI / SI / PR | 84 A6 / 76 A8, 6 PR |
| TL/TT | TT |
| Brand | MRL |
| Tread pattern | MTF 222 |



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- The MRL MTF 222 is a front tractor tyre.
- Its typical tread pattern design with 2 centre ribs and open shoulder lugs provides ride comfort, traction and good self-cleaning.
- Strong casing plies guarantee a long service life for the tyre.

Technical Informations

| | |
|------------------------------|---------------------|
| Item number | 19800274 |
| EAN | 8907375029709 |
| Valid tyre size | 5.00 - 16 |
| LI / SI / PR | 84 A6 / 76 A8, 6 PR |
| TL/TT | TT |
| Brand | MRL |
| Tread pattern | MTF 222 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 7,70 |
| Recommended rim size | 4.00E |
| Maximum air pressure [bar]. | 2,80 |
| Section width (mm) | 140 |
| Outer diameter of tyre [mm]. | 680 |
| Stat. radius (SLR) [mm] | 335 |
| Rolling circumference [mm]. | 2032 |
| Tread depth (mm) | 11,0 |
| Tyre capacity 75% [ltr.] | 17 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 84 A6 | 500 | 30 | | 2,80 | |
| 76 A8 | 400 | 40 | | 2,80 | |