

## TYRES

Product group	Tyres
Item number	19800276
Valid tyre size	5.50 - 16
LI / SI / PR	86 A6 / 78 A8, 6 PR
TL/TT	TT
Brand	MRL
Tread pattern	MTF 221



Bohnenkamp  
■ ■ ● Moving Professionals

## Notes and features

- The MRL MTF 222 is a front tractor tyre.
- It is also suitable for ploughing and transport applications.
- Its typical tread pattern provides very good steering control in the field.

## Technical Informations

Item number	19800276
EAN	8907375030637
Valid tyre size	5.50 - 16
LI / SI / PR	86 A6 / 78 A8, 6 PR
TL/TT	TT
Brand	MRL
Tread pattern	MTF 221
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	10,45
Recommended rim size	4.0E
Permitted rim size	3.50D, 4.50E
Maximum air pressure [bar].	3,70
Section width (mm)	150
Outer diameter of tyre [mm].	710
Stat. radius (SLR) [mm]	330
Rolling circumference [mm].	2135
Tread depth (mm)	14,0
Tyre capacity 75% [ltr.]	19
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
86 A6	530	30		3,70	
78 A8	425	40		3,70	