

TYRES

Product group	Tyres
Item number	19800278
Valid tyre size	6.00 - 16
LI / SI / PR	88 A6 / 80 A8, 6 PR
TL/TT	TT
Brand	MRL
Tread pattern	MTF 222



Notes and features

- The MRL MTF 222 is a front tractor tyre.
- Its typical tread pattern design with 2 centre ribs and open shoulder lugs provides ride comfort, traction and good self-cleaning.
- Strong casing plies guarantee a long service life for the tyre.

Technical Informations

Item number	19800278
EAN	8907375032075
Valid tyre size	6.00 - 16
LI / SI / PR	88 A6 / 80 A8, 6 PR
TL/TT	TT
Brand	MRL
Tread pattern	MTF 222
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	11,30
Recommended rim size	4.5E
Maximum air pressure [bar].	3,30
Section width (mm)	165
Outer diameter of tyre [mm].	735
Stat. radius (SLR) [mm]	355
Rolling circumference [mm].	2220
Tread depth (mm)	15,2
Tyre capacity 75% [litr.]	24
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
88 A6	560	30		3,30	
80 A8	450	40		3,30	