Bohnenkamp Moving Professionals

20.09.2024

TYRES

Product group	Tyres	
Item number	19800279	
Valid tyre size	6.00 - 16	
LI / SI / PR	101 A6 / 97 A8, 6 PR	
TL/TT	тт	
Brand	MRL	
Tread pattern	MIM 374	



Notes and features

- The MRL MIM 374 is an agricultural tyre for tractors, which can also be used on backhoe loaders and agricultural trailers.
- Its curved lugs with wide spaces provide good traction, ride comfort, self-cleaning and a long service life.
- The especially wide lugs enable good ground contact for excellent traction on towing machines.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	19800279
EAN	8907375032013
Valid tyre size	6.00 - 16
LI / SI / PR	101 A6 / 97 A8, 6 PR
TL/TT	TT
Brand	MRL
Tread pattern	MIM 374
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	9,36
Recommended rim size	4.50E
Permitted rim size	4.00E
Maximum air pressure [bar].	2,80
Section width (mm)	169
Outer diameter of tyre [mm].	735
Stat. radius (SLR) [mm]	330
Rolling circumference [mm].	2100
Tread depth (mm)	17,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	23
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
101 A6	825	30		2,80	LLV
97 A8	730	40		2,80	LLV

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.