

TYRES

| Product group | Tyres | |
|-----------------|---------------------|--|
| Item number | 19800280 | |
| Valid tyre size | 6.00 - 16 | |
| LI / SI / PR | 94 A6 / 86 A8, 8 PR | |
| TL/TT | тт | |
| Brand | MRL | |
| Tread pattern | MTF 222 | |



Notes and features

- The MRL MTF 222 is a front tractor tyre.
- Its typical tread pattern design with 2 centre ribs and open shoulder lugs provides ride comfort, traction and good self-cleaning.
- Strong casing plies guarantee a long service life for the tyre.



Technical Informations

| Item number | 19800280 |
|------------------------------|---------------------|
| EAN | 8907375032259 |
| Valid tyre size | 6.00 - 16 |
| LI / SI / PR | 94 A6 / 86 A8, 8 PR |
| TL/TT | тт |
| Brand | MRL |
| Tread pattern | MTF 222 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 11,30 |
| Recommended rim size | 4.5E |
| Maximum air pressure [bar]. | 4,50 |
| Section width (mm) | 165 |
| Outer diameter of tyre [mm]. | 735 |
| Stat. radius (SLR) [mm] | 335 |
| Rolling circumference [mm]. | 2220 |
| Tread depth (mm) | 15,2 |
| Tyre capacity 75% [ltr.] | 24 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 94 A6 | 670 | 30 | | 4,50 | |
| 86 A8 | 530 | 40 | | 4,50 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.