Bohnenkamp Moving Professionals

15.11.2024

TYRES

Product group	Tyres	
Item number	19800282	
Valid tyre size	6.50 - 16	
LI / SI / PR	91 A6 / 83 A8, 6 PR	
TL/TT	TT	
Brand	MRL	
Tread pattern	MTF 221	



Notes and features

- The MRL MTF 222 is a front tractor tyre.
- It is also suitable for ploughing and transport applications.
- Its typical tread pattern provides very good steering control in the field.

Bohnenkamp Moving Professionals

Technical Informations

Item number	19800282	
EAN	8907375034505	
Valid tyre size	6.50 - 16	
LI / SI / PR	91 A6 / 83 A8, 6 PR	
TL/TT	Π	
Brand	MRL	
Tread pattern	MTF 221	
Antistatic	No	
Tyre colour	Black	
ECE regulation number	ECE 106	
Nettogewicht [kg] (gültig)	12,35	
Recommended rim size	4.5E	
Permitted rim size	4.00E, 5K, 5.00F, 5.50F	
Maximum air pressure [bar].	3,10	
Section width (mm)	175	
Outer diameter of tyre [mm].	760	
Stat. radius (SLR) [mm]	355	
Rolling circumference [mm].	2295	
Tread depth (mm)	17,0	
Tyre capacity 75% [ltr.]	26	
E-Ready	No	

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
91 A6	615	30		3,10	
83 A8	487	40		3,10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.